

CS-D at Mont Terri :

The support of the Mont Terri rock laboratory to low carbon economy

Alba Zappone¹⁻², Melchior Grab³, Yves Guglielmi⁵, Claudio Madonna³, Anne Obermann¹, Christophe Nussbaum⁴, Antonio P. Rinaldi¹, C. Roques³, Quinn Wenning³, Stefan Wiemer¹

¹ Swiss Seismological Service, ETHZ, Switzerland; ² Department of Mechanical Engineering, ETHZ, Switzerland; ³ Department of Earth Sciences, ETHZ, Switzerland; ⁴swisstopo, Switzerland; ⁵Energy Geosciences Division, LBNL, USA



ÉCOLE POLYTECHNIQUE
FÉDÉRALE DE LAUSANNE



Schweizerische Eidgenossenschaft
Confédération suisse
Confederazione Svizzera
Confederaziun svizra

Innosuisse – Schweizerische Agentur
für Innovationsförderung




What do we want to learn

Direct observations of fluid migration along a fault and of its interaction with the surrounding environment

Validate instrumentation and methods for **monitoring** and **imaging** fluid transport


Validate Thermo-Hydro-Mechanical-Chemical (THCM) simulations




Why in Mont Terri

- Swiss geological environment
- Underground rock Labs are ideal to bridge between laboratory scale and reservoirsle.
- We can observe «in-situ» and in detail the processes.


centimeter scale




decameter scale



km scale



Concept



Modified after Benson & Cook, 2005

Inject CO₂ saturated water and tracers in Mont Terri main fault:

- Continuous/long term (8-10 month)
- Pulse/ pressure increase steps (at beginning and at end of the injection phase)

Scale: 1-10 m³ water -> rock volume

Monitor injection effects:


- Electrical conductivity, tracers, fluid samples
- Strain = Extensometers, FO
- Pressure
- Microseismic events
- Vp,Vs changes.....

Lab scale mechanical characterization


Numerical simulations (pre and post)

Timeline


CS-D experiment	2019				2020				2021	
	I	II	III	IV	I	II	III	IV	I	II
	Phase 24				Phase 25				Phase 26	
Steps (Phases 24-26):										
Step 1.7 baselines on seismic parameters, pore pressure, temperature, electrical resistivity, pH	■									
Step 2.1: Pulse tests with water		■								
Step 2.2: Steady state injection experiment of CO ₂ enriched water			■	■	■	■	■	■		
Step 2.3: Repeated pulse tests					■	■	■	■		
Step 2.4: monitoring operations with fiber optics, extensometers microseismic, electrical resistivity pH, pressure	■	■	■	■	■	■	■	■		
Step 2.5: fluid sampling and analysis		■	■	■	■	■	■	■		
Step 3.1: sampling boreholes for geochemical/geomechanical analysis (post-mortem)					■	■	■	■	■	
Step 3.2: sealants injections or remediation tests					■	■	■	■	■	
Step 3.3: Data processing and modelling			■	■	■	■	■	■	■	



Installation Instrumentation



A. Zappone



Tectonic fault plane

Sandy Facies

Carbonate-rich Facies


Shaly Facies


Instrumentation

Geophysical borehole monitoring

- 27 Borehole Geophones each with 3-components
- 30 Geophones on the surface (1-component)
- 8 Piezosensors in the boreholes
- 16 Piezosensors on the surface
- Chain extensometers: 12 measuring sections for axial deformation and temperatures
- DSS FO in all boreholes



Geophones: 0.1-2 kHz; piezo: 1-100 kHz






Seismic piezo-sensors




Geophone array



Instrumentation






Phase 1:





Fault characterization & injection tests

by Q. Wenning



Hydraulic characterization

By AP. Rinaldi



Prolonged step test:
- P increased by steps of 300 kPa,
- P_{max} 4800 kPa.
- Step 28/30 hours

Aim: understand the system response to pressurization

Analysis of pressure decay (3 days) : transmissivity in the order of $10^{-13} \text{ m}^2/\text{s}$ ($\sim 10^{-21} \text{ m}^2$ permeability)

The value is closer to previous estimates (Marschall et al. 2003)


Seismic site characterization (D3-D4 crosshole, D3-D5 crosshole)

By M. Grab


Findings:

- Main fault well detectable as a low velocity zone
 - within fault: $V_p = 2200\text{m/s}$
 - below and above: $V_p > 2500\text{ m/s}$
- Reduced anisotropy within the fault
- Anisotropy larger for the foot wall than for the hanging wall, and not a perfect transversely anisotropic media

*Cross-hole V_p -
tomogram
between D3-D5*




Seismic experiments during step-up injection




Decrease in V_p in the vicinity of the injection interval (c.a. 30 m/s)

Interpretation: poroelastic effects during increase of injection pressures (increase of pore pressure => reduction of effective pressure).

A. Zappone



Phase 1:



Deformation and slip during break through

By Y. Guglielmi, D. Rebscher and A.P. Rinaldi



- Different types of optical fiber based sensors:

Bragg for local strain (SIMFIP) •

Brillouin for distributed temperature and strain (DTS and DSS)

Rayleigh for distributed acoustic (DAS)

- 5 bi-axial tiltmeters set at the gallery floor △



Findings:
Reverse shear to the NW
During excavation


About 150 microns shear

Normal opening
After excavation



Some observations from Phase 1

- Fault Transmissivity: $\sim 10^{-13} \text{ m}^2/\text{s}$; Permeability: $\sim 10^{-21} \text{ m}^2$
- Fault opening pressure c.a. 4.8 MPa
- Seismic velocities are sensible to pore pressure variation in the system with c.a. $\sim 1\%$ variation (P waves)
- No seismicity was detected during injection activities
- Fault response to fault excavation (collaboration with FS-B & BGR)

Phase 2:




Injection of CO₂-saturated-fluid: flow-rate





- Constant pressure of 4.5 MPa
- Injection fluid: Pearson water+Kr+CO₂ (mixed at about 2.2 MPa)

Injection of CO₂-saturated-fluid: pressure



- **Time after shut-in (4.5 to 4.2 MPa)**
- **Time after restart (4.8 to 4.5 MPa)**



A. Zappone



Fault self-sealing?
Swelling?

2019

Monitoring dissolved gases with mass-spec




Evidence for injected fluid at monitoring well (CO_2)?

Increased He , indication for the fluid is mixed with formation water?

By C. Roques

Electrical conductivity and pH



	D1	D1+CO ₂	D2
pH	7.05	5.5	7.7
El. Cond (mS/cm)	25.2	23.8	32

Values at atmospheric conditions


At installation: two different waters in boreholes D1 and D2
 Values at equilibrium quite different from atmospheric
 Hard to determine CO₂ arrival at monitoring well.

Some observations from Phase 2

- **Fault decreases in permeability almost immediately ?**
- The spectrometer detects **CO₂** at the monitoring borehole after December.
- pH and EC are hard to interpret
(The current increase in pH after **could indicate fluid-rock interaction**).



Moreover....new “perturbations” to the system are coming....

Phase 2:



Active Rupture patch

Passive Rupture patch



- We need to collect fluid sample from unaffected interval to better understand the evolution
- We need to collect further observation on gas contents
- We need to develop numerical simulation to better understand the pressure evolution

Acknowledgments: We thank Christoph Bärlocher, David Jaeggi, Edgar Manukyan, Hansruedi Maurer, Jocelyn Gisiger, Leo Schwab, Linus Villiger, Maria Kakurina, Marija Lukovic, Nils Knornschild, Nima Gholizadeh, Paul Bossart, Semih Demir, Senecio Schefer, Thierry Theurillat, and Thomas Mörgeli for technical support, scientific advice, and/or on-site assistance. Alessio Ferrari and Alberto Minardi (EPFL) contribute to the project with laboratory analysis. Brice Lecampion and Alexis Saez (EPFL) contribute with numerical simulations.

Further thanks go to all the partners and collaborators of the CS-D experiment:



ACT ELEGANCY, Project No 271498, has received funding from DETEC (CH), BMWi (DE), RVO (NL), Gassnova (NO), BEIS (UK), Gassco, Equinor and Total, and is cofunded by the European Commission under the Horizon 2020 programme, ACT Grant Agreement No 691712.



This project is supported by the pilot and demonstration programme of the Swiss Federal Office of Energy (SFOE). It is conducted within the the Swiss Competence Center for Energy Research – Supply of Electricity (SCCER-SoE / Innosuisse)



Supported by:



Schweizerische Eidgenossenschaft
Confédération suisse
Confederazione Svizzera
Confederaziun svizra
Swiss Confederation
Innosuisse – Swiss Innovation Agency